



GUARDIAN LARGE TRANSIT CASES

NEW!

GUARDIAN IS BUILT STRONGER, LASTS LONGER

THE NEW STANDARD TO PROTECT FROM DUST & HUMIDITY

GUARDIAN CASES ARE WATER TIGHT • CHEMICAL RESISTANT • 30% LIGHTER • CUSTOMIZABLE

The **GUARDIAN** line offers the highest durability in an external case with the specific yet flexible protection inside that individual applications demand. Our creative custom design solutions are proven to meet the demanding, complex needs of some of the toughest industries including the military, aerospace, medical, industrial, energy, oil & gas, electronics, broadcast and telecom fields.

- Recommended for professional applications
- Resistant to chemicals, water, humidity, dust
- Resistant to harsh temperatures (-33°C / +90°C)
- Achieves military standard qualifications
- Wide choice of accessories to customize
- Made of Copolymer Polypropylene compound

STANDARD FEATURES FOR ZG3023, ZG3023D



Two Man Lift Side Handles

Self Oiling Free Running Wheels

Stainless Steel Reinforced Padlockable Points

NEW ZG3023



Guardian 3023		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal Dimensions	mm	770	580	265	90	175	EMPTY ZG-3023-1104-E-B
	inch	30.32	22.83	10.43	3.54	6.89	
External Dimensions	mm	836	641	304			W/STANDARD FOAM ZG-3023-1104-F-B
	inch	32.91	25.24	11.97			
Weight Empty	KG 12.49		LB 27.54				Color: Black Large Front Handle Retractable Handle Removable Lid Jam-free Purge Valve and Latches
Weight w/Foam	KG 14.63		LB 32.25				
Volume	LT 118		GAL 31.17				
Buoyancy	KG/MAX 70		LB/MAX 154.32				
Temp. Rating	°C min -33 max +90		°F min -27.4 max +194				
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						

NEW ZG3023D



Guardian 3023D		LENGTH	WIDTH	DEPTH	LID	BASE	PART NUMBERS
Internal Dimensions	mm	770	580	450	90	360	EMPTY ZG-3023-1804-E-B
	inch	30.32	22.83	17.71	3.54	14.17	
External Dimensions	mm	836	641	489			W/STANDARD FOAM ZG-3023-1804-F-B
	inch	32.91	25.24	19.25			
Weight Empty	KG 15.07		LB 33.22				Color: Black Large Front Handle Retractable Handle Removable Lid Jam-free Purge Valve and Latches
Weight w/Foam	KG 19.47		LB 42.92				
Volume	LT 200		GAL 52.83				
Buoyancy	KG/MAX 144		LB/MAX 317.47				
Temp. Rating	°C min -33 max +90		°F min -27.4 max +194				
Certifications	IP67 · STANAG 4280 (ed. 2) · DEF STAN 81-41 (lev. J)						

GUARDIAN CASES are tested and certified to the following standards:

- Conformity with Directive 2002/95/EC
- DEF STAN 81-41 (level J)
- IP67 Dustproof · Waterproof
- STANAG 4280 (edition 2)


Minimum Order: 30
Standard accessories are available.
Customization and equipment mounting and custom foam options as limitless as your applications require.

Call 1.800.500.9376

Email sales@zerocases.com for Engineering and Design Assistance to Meet Specific Requirements



Both GUARDIAN CASES include a standard Shipping Label Holder



DS-ZG-New 201603

ZERO MANUFACTURING, INC. | 500 West 200 North, North Salt Lake, Utah 84054 USA

Toll Free US 800-500-ZERO (9376) | Direct 801-298-5900 | Fax 801-299-7389 | Email sales@zerocases.com | Web www.zerocases.com